

# according to UK REACH Regulation

#### **EM303**

Revision date: 22.06.2023 Page 1 of 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

EM-303

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Cleaning agent. Flux remover, for the ultrasonic bath, without tensides, concentrate. Restricted to professional users.

#### 1.3. Details of the supplier of the safety data sheet

Company name: EMAG AG Street: Gerauer Str. 34

Place: D-64546 Mörfelden-Walldorf

Telephone: +49(0)6105-406750

e-mail: a.emekci@emag-germany.de
Internet: wwww.emag-germany.de

Responsible Department: info@emag-germany.de, Tel.: +49 (0) 6105 40 67 94

1.4. Emergency telephone 24-hour emergency call, poison control Berlin: 030-30686700

number:

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Skin Irrit. 2; H315 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

# **GB CLP Regulation**

## Hazard components for labelling

Disodium metasilicate pentahydrat Sodium hydroxide; caustic soda **Signal word:** Danger

Pictograms:



## **Hazard statements**

H315 Causes skin irritation.H318 Causes serious eye damage.

# **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures



# according to UK REACH Regulation

# EM303

Revision date: 22.06.2023 Page 2 of 9

#### **Hazardous components**

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation				
7732-18-5	Water			80-90 %	
	231-791-2				
497-19-8	sodium carbonate			<5,0 %	
	207-838-8	011-005-00-2	01-2119485498-19		
	Eye Irrit. 2; H319				
10213-79-3	Disodium metasilicate pentahydrat			<3,0 %	
	600-279-4		01-2119449811-37		
	Met. Corr. 1, Skin Corr. 1B, Eye Da				
1310-73-2	Sodium hydroxide; caustic soda	<1,0 %			
	215-185-5	011-002-00-6	01-2119457892-27		
	Skin Corr. 1A; H314				
1336-21-6	ammonia %	<2,5 %			
	215-647-6		01-2119488876-14		
	Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, STOT SE 3, Aquatic Acute 1; H290 H314 H318 H335 H400				
22042-96-2	Phosphonate	<2,0 %			
	244-751-4		01-2119514449-36		

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Conc.	Limits, M-factors and ATE				
497-19-8	97-19-8 207-838-8 sodium carbonate					
	dermal: LD50 = >2000 mg/kg; oral: LD50 = 2800 mg/kg					
10213-79-3	600-279-4	-4 Disodium metasilicate pentahydrat				
	dermal: LD50 = >5000 mg/kg; oral: LD50 = 1349 mg/kg					
1310-73-2	215-185-5	Sodium hydroxide; caustic soda	<1,0 %			
	I	000 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5				
	Skin Irrit. 2; H3	:15: >= 0,5 - < 2				

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

# **General information**

Change contaminated clothing.

# After inhalation

Provide fresh air.

# After contact with skin

After contact with skin, wash immediately with plenty of Water and soap.

# After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. In case of troubles or persistent symptoms, consult an opthalmologist.



# according to UK REACH Regulation

#### **EM303**

Revision date: 22.06.2023 Page 3 of 9

#### After ingestion

Rinse mouth immediately and drink large quantities of water. Do not induce vomiting. Consult physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

No symptoms known up to now.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

# Suitable extinguishing media

Water. Foam. Atomized water.

#### Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Nitrogen oxides (NOx). Carbon dioxide (CO2).

#### 5.3. Advice for firefighters

Protective clothing.

#### Additional information

Material is not combustible. Extinguishing materials should be selected according to the surrounding area.

## **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

# General advice

Wear personal protection equipment.

# 6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

# 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the assimilated material according to the section on waste disposal.

# 6.4. Reference to other sections

See protective measures under point 7 and 8.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

# Advice on safe handling

No special technical protective measures are necessary.

## Advice on protection against fire and explosion

Product is not: Oxidizing. Flammable. explosive.

# Advice on general occupational hygiene

Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and at the end of work.

# 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Store only in original container. Keep away from food, drink and animal feedingstuffs.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters



# according to UK REACH Regulation

# **EM303**Revision date: 22.06.2023 Page 4 of 9

# **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin	
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	WEL	ĺ

# **DNEL/DMEL values**

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
497-19-8	sodium carbonate						
Worker DNEL,	long-term	inhalation	systemic	10 mg/m³			
Consumer DNE	EL, long-term	inhalation	systemic	10 mg/m³			
10213-79-3	Disodium metasilicate pentahydrat						
Consumer DNE	EL, long-term	oral	systemic	0,74 mg/kg bw/day			
Worker DNEL,	long-term	dermal	systemic	1,49 mg/kg bw/day			
Consumer DNE	EL, long-term	inhalation	systemic	1,55 mg/m³			
Worker DNEL,	long-term	inhalation	systemic	6,22 mg/m³			
1310-73-2	Sodium hydroxide; caustic soda						
Worker DNEL,	long-term	inhalation	local	1 mg/m³			
Consumer DNE	EL, long-term	inhalation	local	1 mg/m³			
1336-21-6	ammonia %						
Worker DNEL, acute		inhalation	local	47,6 mg/m³			
Consumer DNEL, acute		inhalation	local	23,8 mg/m³			
22042-96-2	22042-96-2 Phosphonate						
Consumer DNE	EL, long-term	oral	systemic	1,9 mg/kg bw/day			
Consumer DNE	EL, acute	oral	systemic	1,9 mg/kg bw/day			

# PNEC values

CAS No	Substance					
Environmental	compartment	Value				
10213-79-3 Disodium metasilicate pentahydrat						
Freshwater	Freshwater					
Marine water	Marine water					
Micro-organism	1000 mg/l					
1336-21-6 ammonia %						
Freshwater						
22042-96-2	Phosphonate					
Freshwater		0,52 mg/l				
Marine water		0,052 mg/l				
Freshwater sediment 108 mg/kg						
Marine sediment 10,8 mg						
Micro-organisms in sewage treatment plants (STP)						
Soil						

# 8.2. Exposure controls



# according to UK REACH Regulation

#### **EM303**

Revision date: 22.06.2023 Page 5 of 9

#### Appropriate engineering controls

Refer to chapter 7. No further action is necessary.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear eye/face protection.

#### Hand protection

Suitable material:

PE (polyethylene).Layer thickness: 0,5 mm penetration time (maximum wearing period): >=8h

CR (polychloroprenes, Chloroprene rubber). 0,5 mm penetration time (maximum wearing period): >=8h

NBR (Nitrile rubber). 0,35 mm penetration time (maximum wearing period): >=8h

Butyl rubber. FKM (Fluoroelastomer (Viton)). 0,5 mm penetration time (maximum wearing period): >=8h

Breakthrough times and swelling characteristics of the material must be taken into consideration.

Recommended protective gloves brand: Camapren 722, Manufacturer: KCL, or comparable makes from other companies.

#### Skin protection

Skin protection: not required.

## Respiratory protection

Respiratory protection not required.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: clear, yellow
Odour: like: Ammonia

Test method

Melting point/freezing point:

-6 °C

Boiling point or initial boiling point and

>100 °C

boiling range:

Flash point:

pH-Value (at 20 °C): 13,5 (conc.) 11,5 (1 %) DGF H-III 1

Water solubility: complete miscible

Density (at 20 °C): 1,085 g/cm³ DIN 12791

# 9.2. Other information

# Information with regard to physical hazard classes

Explosive properties not Explosive.
Oxidizing properties not oxidizing.

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Exothermic reactions with: acid, concentrated.

# 10.2. Chemical stability

The product is chemically stable under normal ambient conditions.

# 10.3. Possibility of hazardous reactions

None, in case of proper use.

## 10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapors.



according to UK REACH Regulation

#### EM303

Revision date: 22.06.2023 Page 6 of 9

# 10.5. Incompatible materials

acid, concentrated.

# 10.6. Hazardous decomposition products

None, in case of proper use.

#### **Further information**

Do not mix with other products.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
497-19-8	sodium carbonate							
	oral	LD50 2 mg/kg	2800	rat				
	dermal	LD50 : mg/kg	>2000					
10213-79-3	Disodium metasilicate pe	ntahydrat						
	oral	LD50 mg/kg	1349	rat				
	dermal		>5000	rat		EPA OPPTS 870.1200		
1310-73-2	Sodium hydroxide; caustic soda							
	oral	LD50 2 mg/kg	2000	rat				

# Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Risk of serious damage to eyes.

Irritant effect on the skin: irritant.

# Sensitising effects

Based on available data, the classification criteria are not met. no danger of sensitization.

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

# **Aspiration hazard**

Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Technically correct releases of minimal concentrations to adapted biological sewage treatment facility, will not disturb the biodegradability of activated sludge. due to the alkaline character of the product, usually, it has to be neutralized before contaminated effluents are introduced into the waste water treatment system.



# according to UK REACH Regulation

#### EM303

Revision date: 22.06.2023 Page 7 of 9

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
497-19-8	sodium carbonate						
	Acute fish toxicity	LC50	300 mg/l	96 h	Lepomis macrochirus	msds	
	Acute crustacea toxicity	EC50	200 mg/l	48 h	Daphnia magna	msds	
10213-79-3	Disodium metasilicate per	ntahydrat					
	Acute fish toxicity	LC50	210 mg/l	96 h	Danio rerio		ISO 7346/1
	Acute algae toxicity ErC50 >345,4 mg/l			Scenedesmus subspicatus		DIN 38412	
	Acute crustacea toxicity	toxicity EC50 1700 48 h Daphnia magna					
1310-73-2	Sodium hydroxide; causti	c soda					
	Acute fish toxicity	LC50	125 mg/l	96 h	Gambusia affinis	SDB Lieferant	
	Acute crustacea toxicity	EC50 mg/l	40,4	48 h	Ceriodaphnia	ECHA	
1336-21-6	ammonia %						
	Acute fish toxicity	LC50 mg/l	0,89	96 h		msds	
	Acute crustacea toxicity	EC50	48 mg/l	48 h		msds	
	Crustacea toxicity NOEC 0,42 mg/l		21 d	Daphnia magna	msds		

#### 12.2. Persistence and degradability

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

#### 12.3. Bioaccumulative potential

On the basis of existing data about disposal/decomposition and bio-accumulation potential, long term environmental damage is unlikely.

## 12.4. Mobility in soil

No data available

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. not applicable

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# 12.7. Other adverse effects

No data available

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

## **Disposal recommendations**

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

# List of Wastes Code - residues/unused products

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately

collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste



# according to UK REACH Regulation

#### **EM303**

Revision date: 22.06.2023 Page 8 of 9

#### List of Wastes Code - used product

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND

INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

#### Contaminated packaging

Completely emptied packings can be re-cycled.

## **SECTION 14: Transport information**

#### Other applicable information

Not a hazardous material with respect to transportation regulations.

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2004/42/EC (VOC): 0 % (0 g/l)

**National regulatory information** 

Water hazard class (D): 1 - slightly hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Changes

Data changed from previous versions: 1.1., 1.4., 2.1., 3.2., 7.1., 8.2., 9.1., 9.2., 11.1., 12.1., 12.2., 12.5., 12.6., 12.7., 15.1., 16.

# Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method

# Relevant H and EUH statements (number and full text)

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.

#### **Further Information**

Training instructions: Notice the directions for use on the label.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.



# according to UK REACH Regulation

# EM303

Revision date: 22.06.2023 Page 9 of 9

# Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	EM-303	IS, PW	0	35	8a, 9, 13	8a	0	26	

 LCS: Life cycle stages
 SU: Sectors of use

 PC: Product categories
 PROC: Process categories

 ERC: Environmental release categories
 AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Revision No: 1,05 GB - en Print date: 22.06.2023